EVERYTHING YOU WANT IN A COMPACT TRACTOR

FREQUENTLY ASKED QUESTIONS

Q. WHO MAKES THE TRACTOR?

A. Our Tractors are made to Summit's exact specifications by ITL, manufacturers of quality tractors sold worldwide. Our engines are made by Mitsubishi, and the Goodyear tire & wheel assemblies are made in the U.S. by industry leader Titan

Q. WHERE DO I GET IT SERVICED?

A. Summit Tractors has partnered with Service Dealers located near every location that Summit Tractors are sold. Providing quality service is our top priority

Q. WHAT IS THE WARRANTY?

A. Summit Tractors have the industry's longest full machine warranty at 3 years or 2000 hours and a very competitive limited powertrain warranty of 6 years or 3000 hours

Q. HOW DOES THIS TRACTOR COMPARE TO OTHER NAME BRANDS?

A. Summit Tractors have more standard features than any tractor in its HP class, with levels of performance and quality equal to or better than that of any other brand

Q. DO YOU OFFER FINANCING?

A. No down payment financing is available. See store or visit the financing section of summittractors.com for more information



READY TO GO TO WORK

- 24.7 HP Mitsubishi EPA Tier 4
 Diesel Engine
- 18 PTO HP, Rear 540 RPM, Mid 2100 RPM
- Hydrostatic Transmission with Side-By-Side Pedals
- One Set Self-Canceling Detent Rear Hydraulic Remotes
- Cruise Control
- 4WD With Differential Lock
- RimGuard™ Liquid Tire Ballast Rear Tires
- 3rd Function Loader Valve with Integrated Joystick

 Projector Headlamps and Rear Work Light

SUMMIT.

- Skid-Steer Quick Attach and Self-Leveling Loader
- 7-Point Trailer Connector and Front Tow Hook
- Goodyear All Condition R14 Tires
- Foldable and Removeable Side-View Mirrors
- Category 1 3-Pt Hitch with Swinging and Bar Drawbars
- Premium Adjustable Suspension Seat





THE INDUSTRY'S LONGEST FULL MACHINE WARRANTY

Full Machine: 3 years or 2000 Hours Limited Powertrain: 6 years or 3000 Hours











SUMMIT TX25H TRACTOR SPECIFICATIONS AND STANDARD FEATURES

201411111111111111111111111111111111111	RAUTUR SPECIFI
ENGINE	
Engine Manufacturer	Mitsubishi
Engine Type	Natural Aspiration
Gross Engine Power, HP (kw)	24.7 (18.4)
PTO, HP (kw)	18 (13.4)
Rated Engine Speed	2500
Number of Cylinders	3
Displacement, cu.in. (cc)	80.42 (1318)
Cooling System	Liquid
Air Cleaner	Dual Element
Alternator	12V42A
Starting Aid	Glow Plug
Fuel System Type	Indirect Fuel Injection
	-
Fuel Tank Capacity, U.S. gal. (L)	6.9 (26)
POWERTRAIN	0.0
Transmission Type	2-Range Hydrostatic
Forward/Reverse Foot Control	Side-by-Side Pedals
Cruise Control	Standard
Max Traveling Speed, mph (km/h)	11.32 (18.22)
Brakes	Wet Disc
Steering	Hydraulic
HYDRAULIC SYSTEM	
Pump Type	Open Center
Implement Flow, gpm (L/Min)	4.8 (18.2)
Category, 3-Point Hitch	1
3-Pt. Hitch Lift Capacity, lb. (kg)	1322 (600)
At 24 Inches Behind Link Ends, lb. (kg)	1168 (530)
Lift Control type	Position Control
Rear Remote Valves	1 Set Self-Canceling Detent Standard
3rd Function Diverter Valve	Standard w/ Loader
РТО	
РТО Туре	Independent
PTO Control	Electric/Hydro
PTO Mid (rpm)	2100
PTO Rear (rpm)	540
PTO Shaft Diameter in. (mm)	1 3/8 (35)
OTHER	1 3/0 (33)
Cross-Bar Type Drawbar	Standard
Swinging Drawbar	Standard
Front Tow Hook	Standard
Hood and Fenders Material	Metal
Rimguard™ Liquid Tire Ballast Rear Tires	Standard
DIMENSIONS Out the second of	440 / /000 //
Overall Length, in. (mm) with R14T Tires	113.6 (2886)
Overall Width, in. (mm) with R14T Tires	54 (1372)
Wheelbase, in. (mm) with R14T Tires	61.8 (1570)
Height to Top of ROPS, in. (mm) R14T Tires	92.1 (2340)
Min. Ground Clearance, in. (mm) R14T Tires	9.6 (245) Front Axle
Total Weight, lb (kg) R14T Tires & Wheels	2513 (1140)
	2513 (1140) 152 (3861)

Front Goodyear R14T 23x8.50-12 (USA) Rear Goodyear R14T 12-16.5 (USA) OPERATOR STATION Roll Over Protection Structure (ROPS) Type Folding Premium Projector Headlamps Standard Rear Work Light Standard High Back Seat with Backrest Extension Standard Dial by Operator Weight Seat Suspension Adjustment Standard Angle Adjustable & Folding Seat Armrests Standard Seat Cover Type Coated PVC Weatherproof Side View Mirrors Standard Entry Assist Steps & Grab Rails Both Sides Standard 12V Power Outlet & Cup Holder Standard Max Lifting Height at Pivot Point in. (mm) 83 (2108) Clearance with Attachment Dump in. (mm) 61 (1550) Reach at Maximum Height in. (mm) 34 (860) Reach at Bucket on Ground in. (mm) 63.4 (1610) Max. Dump Angle (Deg.) 41 Breakout Force at Pivot Point (dig position) Ib. (kg) Bucket Width in. (mm) 48 (1220) Lifting Capacity to Full Height at Pivot Point Ib. (kg) Bucket Connection Type Skid Steer Quick Attach Attach Attach Standard WARRANTY Tractor - Full Machine 3 Years or 2000 Hours Front-End Loader 1 Year	STANDARD TIRES		
PERATOR STATION Roll Over Protection Structure (ROPS) Type Premium Projector Headlamps Rear Work Light Standard High Back Seat with Backrest Extension Dial by Operator Weight Seat Suspension Adjustment Angle Adjustable & Folding Seat Armrests Standard Seat Cover Type Coated PVC Weatherproof Side View Mirrors Standard Entry Assist Steps & Grab Rails Both Sides Standard Entry Assist Steps & Grab Rails Both Sides Standard FRONT-END LOADER Model LX85 Mechanical Self-Leveling Max Lifting Height at Pivot Point in. (mm) Clearance with Attachment Dump in. (mm) Reach at Maximum Height in. (mm) Ass. Dump Angle (Deg.) Attachment Rollback Angle (Deg) Breakout Force at Pivot Point (dig position) Ib. (kg) Lifting Capacity to Full Height at Pivot Point Ib. (kg) Bucket Width in. (mm) Standard MARANTY Tractor - Full Machine Tractor - Limited Powertrain Standard Standard Attachment Tollouse Attachment Standard Attachment Rollback Angle Attachment Rollback Angle Standard Attachment Rollback A	Front	_	
Roll Over Protection Structure (ROPS) Type Premium Projector Headlamps Standard Rear Work Light Standard High Back Seat with Backrest Extension Dial by Operator Weight Seat Suspension Adjustment Angle Adjustable & Folding Seat Armrests Standard Seat Cover Type Coated PVC Weatherproof Side View Mirrors Standard Entry Assist Steps & Grab Rails Both Sides Standard 12V Power Outlet & Cup Holder FRONT-END LOADER Model LX85 Mechanical Self-Leveling Max Lifting Height at Pivot Point in. (mm) Clearance with Attachment Dump in. (mm) Assi, at Maximum Height in. (mm) Breakout Force at Pivot Point (dig position) Ib. (kg) Bucket Width in. (mm) As (1220) Lifting Capacity to Full Height at 500mm Ahead of Pivot Point Ib. (kg) Bucket Connection Type Skid Steer Quick Attach Bucket Level Indicator Standard Ayears or 2000 Hours Tractor - Full Machine Tractor - Limited Powertrain Standard Standard Standard Standard Standard Standard Standard Standard Standard Attachment Rollback Angle (Deg.) 42 Attachment Rollback Angle (Deg) 41 Breakout Force at Pivot Point (dig position) Ib. (kg) Standard Attachment Rollback Angle (Deg) Skid Steer Quick Attach Standard WARRANTY Tractor - Full Machine Tractor - Limited Powertrain 6 Years or 3000 Hours	Rear	Goodyear R14T 12-16.5 (USA)	
Premium Projector Headlamps Rear Work Light Standard High Back Seat with Backrest Extension Dial by Operator Weight Seat Suspension Adjustment Angle Adjustable & Folding Seat Armrests Retractable Seat Belt Standard Seat Cover Type Coated PVC Weatherproof Side View Mirrors Standard Entry Assist Steps & Grab Rails Both Sides Standard 12V Power Outlet & Cup Holder FRONT-END LOADER Model LX85 Mechanical Self-Leveling Max Lifting Height at Pivot Point in. (mm) Reach at Maximum Height in. (mm) Reach at Bucket on Ground in. (mm) Breakout Force at Pivot Point (dig position) Ib. (kg) Bucket Width in. (mm) 48 (1220) Lifting Capacity to Full Height at 500mm Ahead of Pivot Point Ib. (kg) Bucket Level Indicator WARRANTY Tractor - Full Machine Tractor - Limited Powertrain Standard Standar	OPERATOR STATION		
Rear Work Light High Back Seat with Backrest Extension Dial by Operator Weight Seat Suspension Adjustment Angle Adjustable & Folding Seat Armrests Retractable Seat Belt Standard Seat Cover Type Coated PVC Weatherproof Side View Mirrors Standard Entry Assist Steps & Grab Rails Both Sides Standard 12V Power Outlet & Cup Holder FRONT-END LOADER Model LX85 Mechanical Self-Leveling Max Lifting Height at Pivot Point in. (mm) Clearance with Attachment Dump in. (mm) Reach at Maximum Height in. (mm) Ax. Dump Angle (Deg.) Attachment Rollback Angle (Deg) Breakout Force at Pivot Point (dig position) Ib. (kg) Bucket Width in. (mm) As (120) Lifting Capacity to Full Height at 500mm Ahead of Pivot Point Ib. (kg) Bucket Connection Type Skid Steer Quick Attach WARRANTY Tractor - Full Machine Tractor - Limited Powertrain Standard Standard Standard Attachment Rollback Angle Standard Attachment Rollback Angle Attachment Rollback Angle Skid Steer Quick Attach Standard WARRANTY Tractor - Full Machine Tractor - Limited Powertrain 6 Years or 3000 Hours	Roll Over Protection Structure (ROPS) Type	Folding	
High Back Seat with Backrest Extension Dial by Operator Weight Seat Suspension Adjustment Angle Adjustable & Folding Seat Armrests Retractable Seat Belt Standard Seat Cover Type Coated PVC Weatherproof Side View Mirrors Standard Entry Assist Steps & Grab Rails Both Sides Standard Entry Assist Steps & Grab Rails Both Sides Standard Entry Assist Steps & Grab Rails Both Sides Standard Entry Assist Steps & Grab Rails Both Sides Standard Entry Assist Steps & Grab Rails Both Sides Standard Entry Assist Steps & Grab Rails Both Sides Standard Entry Assist Steps & Grab Rails Both Sides Standard Entry Assist Steps & Grab Rails Both Sides Standard Entry Assist Steps & Grab Rails Both Sides Standard Entry Assist Steps & Grab Rails Both Sides Standard Entry Assist Steps & Grab Rails Both Sides Standard Entry Assist Steps & Grab Rails Both Sides Standard Entry Assist Steps & Grab Rails Both Sides Standard Entry Assist Steps & Grab Rails Both Sides Standard Entry Assist Steps & Grab Rails Both Sides Standard Entry Assist Steps & Grab Rails Both Sides Standard Max Lifting Height at Pivot Point (Intro Intro	Premium Projector Headlamps	Standard	
Dial by Operator Weight Seat Suspension Adjustment Angle Adjustable & Folding Seat Armrests Retractable Seat Belt Standard Seat Cover Type Coated PVC Weatherproof Side View Mirrors Standard Heavy Duty Rubber Floor Mat Entry Assist Steps & Grab Rails Both Sides Standard 12V Power Outlet & Cup Holder FRONT-END LOADER Model LX85 Mechanical Self-Leveling Standard Max Lifting Height at Pivot Point in. (mm) Clearance with Attachment Dump in. (mm) Reach at Maximum Height in. (mm) Max. Dump Angle (Deg.) Attachment Rollback Angle (Deg) Breakout Force at Pivot Point (dig position) 1b. (kg) Bucket Width in. (mm) Lifting Capacity to Full Height at Pivot Point Ib. (kg) Bucket Connection Type Skid Steer Quick Attach Bucket Level Indicator WARRANTY Tractor - Full Machine Tractor - Limited Powertrain Standard Standard Standard Atandard Standard Atandard Standard Atandard Standard Atandard Standard Atandard Standard Atandard Standard Standard Standard Standard Standard Atandard Standard Atandard Atandar	Rear Work Light	Standard	
Suspension Adjustment Angle Adjustable & Folding Seat Armrests Retractable Seat Belt Seat Cover Type Coated PVC Weatherproof Side View Mirrors Standard Heavy Duty Rubber Floor Mat Entry Assist Steps & Grab Rails Both Sides Standard 12V Power Outlet & Cup Holder FRONT-END LOADER Model LX85 Mechanical Self-Leveling Standard Max Lifting Height at Pivot Point in. (mm) Clearance with Attachment Dump in. (mm) Reach at Maximum Height in. (mm) Max. Dump Angle (Deg.) Attachment Rollback Angle (Deg) Breakout Force at Pivot Point (dig position) 16. (kg) Bucket Width in. (mm) Lifting Capacity to Full Height at Pivot Point Ib. (kg) Bucket Connection Type Skid Steer Quick Attach Bucket Level Indicator WARRANTY Tractor - Full Machine Tractor - Limited Powertrain Standard Standard Standard Attandard Atta	High Back Seat with Backrest Extension	Standard	
Retractable Seat Belt Seat Cover Type Coated PVC Weatherproof Side View Mirrors Standard Heavy Duty Rubber Floor Mat Standard Entry Assist Steps & Grab Rails Both Sides Standard 12V Power Outlet & Cup Holder Standard FRONT-END LOADER Model LX85 Mechanical Self-Leveling Standard Max Lifting Height at Pivot Point in. (mm) Reach at Maximum Height in. (mm) Reach at Bucket on Ground in. (mm) Max. Dump Angle (Deg.) Attachment Rollback Angle (Deg) Breakout Force at Pivot Point (dig position) Ib. (kg) Bucket Width in. (mm) Lifting Capacity to Full Height at Pivot Point Ib. (kg) Bucket Connection Type Skid Steer Quick Attach Bucket Level Indicator WARRANTY Tractor - Full Machine Tractor - Limited Powertrain Standard Standard Coated PVC Weatherproof Standard WARRANTY Tractor - Full Machine Tractor - Limited Powertrain Standard		Standard	
Seat Cover Type Side View Mirrors Side View Mirrors Standard Standard Standard Entry Assist Steps & Grab Rails Both Sides Standard 12V Power Outlet & Cup Holder FRONT-END LOADER Model LX85 Mechanical Self-Leveling Max Lifting Height at Pivot Point in. (mm) Standard Reach at Maximum Height in. (mm) Reach at Bucket on Ground in. (mm) Max. Dump Angle (Deg.) Attachment Rollback Angle (Deg) Breakout Force at Pivot Point (dig position) Ib. (kg) Bucket Width in. (mm) At (120) Lifting Capacity to Full Height at Pivot Point Ib. (kg) Bucket Connection Type Skid Steer Quick Attach Bucket Level Indicator Standard WARRANTY Tractor - Full Machine Tractor - Limited Powertrain Standard	Angle Adjustable & Folding Seat Armrests	Standard	
Side View Mirrors Heavy Duty Rubber Floor Mat Entry Assist Steps & Grab Rails Both Sides Standard 12V Power Outlet & Cup Holder FRONT-END LOADER Model LX85 Mechanical Self-Leveling Max Lifting Height at Pivot Point in. (mm) Clearance with Attachment Dump in. (mm) Reach at Maximum Height in. (mm) Max. Dump Angle (Deg.) Attachment Rollback Angle (Deg) Breakout Force at Pivot Point (dig position) lb. (kg) Bucket Width in. (mm) Lifting Capacity to Full Height at Pivot Point lb. (kg) Bucket Connection Type Skid Steer Quick Attach WARRANTY Tractor - Full Machine Tractor - Limited Powertrain Standard Standard Standard Standard MAX Standard Attachment Rollback Angle (Deg) 41 1477 (670) 1477 (670) 1102 (500) Skid Steer Quick Attach Standard WARRANTY Tractor - Full Machine 3 Years or 2000 Hours Tractor - Limited Powertrain 6 Years or 3000 Hours	Retractable Seat Belt	Standard	
Heavy Duty Rubber Floor Mat Entry Assist Steps & Grab Rails Both Sides Standard 12V Power Outlet & Cup Holder FRONT-END LOADER Model Max Lifting Height at Pivot Point in. (mm) Clearance with Attachment Dump in. (mm) Reach at Maximum Height in. (mm) Max. Dump Angle (Deg.) Breakout Force at Pivot Point (dig position) Ib. (kg) Bucket Width in. (mm) Lifting Capacity to Full Height at Pivot Point Ib. (kg) Bucket Connection Type Skid Steer Quick Attach WARRANTY Tractor - Full Machine Tractor - Limited Powertrain Standard Both Sides Standard Both Sides Standard Nath Sides Standard Both Sides Standard Both Sides Standard Nath Sides Standard Nath Sides Standard Both Sides Standard Nath Sides Standard N	Seat Cover Type	Coated PVC Weatherproof	
Entry Assist Steps & Grab Rails 12V Power Outlet & Cup Holder FRONT-END LOADER Model LX85 Mechanical Self-Leveling Max Lifting Height at Pivot Point in. (mm) Clearance with Attachment Dump in. (mm) Reach at Maximum Height in. (mm) Max. Dump Angle (Deg.) Attachment Rollback Angle (Deg) Breakout Force at Pivot Point (dig position) llb. (kg) Bucket Width in. (mm) Lifting Capacity to Full Height at Pivot Point lb. (kg) Bucket Connection Type Skid Steer Quick Attach Bucket Level Indicator WARRANTY Tractor - Full Machine Tractor - Limited Powertrain LX85 Both Sides Standard Standard Example Standard Both Sides Standard Standard Both Sides Standard Standard Bux85 Both Sides Standard Standard Bux85 Both Sides Standard Bux85 Standard Bux85 Both Sides Standard Bux85 Standard Bux85 Both Sides Standard Bux85 Standard Bux85 Both Sides Standard Bux86 Both Sides Standard Bux85 Both Standard Bux85 Both Standard Bux86 Bux86 Both Standard Bux86 Both Sides Bux86 Bux86 Both Sides B	Side View Mirrors	Standard	
12V Power Outlet & Cup Holder FRONT-END LOADER Model Max Lifting Height at Pivot Point in. (mm) Clearance with Attachment Dump in. (mm) Reach at Maximum Height in. (mm) Max. Dump Angle (Deg.) Attachment Rollback Angle (Deg) Breakout Force at Pivot Point (dig position) llb. (kg) Bucket Width in. (mm) Lifting Capacity to Full Height at Pivot Point lb. (kg) Lifting Capacity to Full Height at 500mm Ahead of Pivot Point lb. (kg) Bucket Connection Type Skid Steer Quick Attach Bucket Level Indicator WARRANTY Tractor - Full Machine Tractor - Limited Powertrain Lix85 Lix85 Lix85 Lix85 Mechanical Lix85 Lix85 Lix85 Lix85 Standard 84 (2108) 64 (11550) 84 (4610) 84 (4610) 84 (4610) 84 (1610) 1477 (670) 1477 (670) 1477 (670) 1477 (670) 148 (1220) 1102 (500) 1234 (560) 84 (1230) 1234 (560) 84 (1230) 1234 (560) 84 (1230) 1234 (560) 84 (1230) 1234 (560) 85 (1230) 86 (1230) 87 (1230) 87 (1230) 88 (1230) 89 (1230) 1231 (1230) 1232 (1230) 1234	Heavy Duty Rubber Floor Mat	Standard	
Model Model LX85 Mechanical Self-Leveling Max Lifting Height at Pivot Point in. (mm) Clearance with Attachment Dump in. (mm) Reach at Maximum Height in. (mm) Reach at Bucket on Ground in. (mm) Max. Dump Angle (Deg.) Attachment Rollback Angle (Deg) Breakout Force at Pivot Point (dig position) Ib. (kg) Bucket Width in. (mm) Lifting Capacity to Full Height at Pivot Point lb. (kg) Lifting Capacity to Full Height at 500mm Ahead of Pivot Point Ib. (kg) Bucket Connection Type Skid Steer Quick Attach Bucket Level Indicator WARRANTY Tractor - Full Machine Tractor - Limited Powertrain 6 Years or 3000 Hours	Entry Assist Steps & Grab Rails	Both Sides Standard	
Model LX85 Mechanical Self-Leveling Standard Max Lifting Height at Pivot Point in. (mm) 83 (2108) Clearance with Attachment Dump in. (mm) 61 (1550 Reach at Maximum Height in. (mm) 34 (860) Reach at Bucket on Ground in. (mm) 63.4 (1610) Max. Dump Angle (Deg.) 42 Attachment Rollback Angle (Deg) 41 Breakout Force at Pivot Point (dig position) 1477 (670) Bucket Width in. (mm) 48 (1220) Lifting Capacity to Full Height at Pivot Point lb. (kg) Lifting Capacity to Full Height at 500mm Ahead of Pivot Point lb. (kg) Bucket Connection Type Skid Steer Quick Attach Bucket Level Indicator Standard WARRANTY Tractor - Full Machine 3 Years or 2000 Hours Tractor - Limited Powertrain 6 Years or 3000 Hours	12V Power Outlet & Cup Holder	Standard	
Mechanical Self-Leveling Max Lifting Height at Pivot Point in. (mm) Clearance with Attachment Dump in. (mm) Reach at Maximum Height in. (mm) Reach at Bucket on Ground in. (mm) Max. Dump Angle (Deg.) Attachment Rollback Angle (Deg) Breakout Force at Pivot Point (dig position) Ib. (kg) Bucket Width in. (mm) Lifting Capacity to Full Height at Pivot Point Ib. (kg) Lifting Capacity to Full Height at 500mm Ahead of Pivot Point Ib. (kg) Bucket Connection Type Skid Steer Quick Attach Bucket Level Indicator WARRANTY Tractor - Full Machine 3 Years or 2000 Hours Tractor - Limited Powertrain 6 Years or 3000 Hours	FRONT-END LOADER		
Max Lifting Height at Pivot Point in. (mm) Clearance with Attachment Dump in. (mm) Reach at Maximum Height in. (mm) Reach at Bucket on Ground in. (mm) Max. Dump Angle (Deg.) Attachment Rollback Angle (Deg) Breakout Force at Pivot Point (dig position) Ib. (kg) Bucket Width in. (mm) Lifting Capacity to Full Height at Pivot Point Ib. (kg) Lifting Capacity to Full Height at 500mm Ahead of Pivot Point Ib. (kg) Bucket Connection Type Skid Steer Quick Attach Bucket Level Indicator WARRANTY Tractor - Full Machine Tractor - Limited Powertrain 6 Years or 3000 Hours	Model	LX85	
Clearance with Attachment Dump in. (mm) Reach at Maximum Height in. (mm) Reach at Bucket on Ground in. (mm) Max. Dump Angle (Deg.) Attachment Rollback Angle (Deg) Breakout Force at Pivot Point (dig position) Ib. (kg) Bucket Width in. (mm) Lifting Capacity to Full Height at Pivot Point Ib. (kg) Lifting Capacity to Full Height at 500mm Ahead of Pivot Point Ib. (kg) Bucket Connection Type Skid Steer Quick Attach Bucket Level Indicator WARRANTY Tractor - Full Machine Tractor - Limited Powertrain 6 Years or 3000 Hours	Mechanical Self-Leveling	Standard	
Reach at Maximum Height in. (mm) Reach at Bucket on Ground in. (mm) Max. Dump Angle (Deg.) Attachment Rollback Angle (Deg) Breakout Force at Pivot Point (dig position) lb. (kg) Bucket Width in. (mm) Lifting Capacity to Full Height at Pivot Point lb. (kg) Lifting Capacity to Full Height at 500mm Ahead of Pivot Point lb. (kg) Bucket Connection Type Skid Steer Quick Attach Bucket Level Indicator WARRANTY Tractor - Full Machine Tractor - Limited Powertrain 34 (860) 43 (1610) 44 (177 (670) 1477 (670) 1477 (670) 1477 (670) 1477 (670) 1477 (670) 1477 (670) Skid (1220) 1102 (500) 1234 (560) Skid Steer Quick Attach Standard	Max Lifting Height at Pivot Point in. (mm)	83 (2108)	
Reach at Bucket on Ground in. (mm) Max. Dump Angle (Deg.) Attachment Rollback Angle (Deg) Breakout Force at Pivot Point (dig position) lb. (kg) Bucket Width in. (mm) Lifting Capacity to Full Height at Pivot Point lb. (kg) Lifting Capacity to Full Height at 500mm Ahead of Pivot Point lb. (kg) Bucket Connection Type Skid Steer Quick Attach Bucket Level Indicator WARRANTY Tractor - Full Machine Tractor - Limited Powertrain 6 Years or 3000 Hours	Clearance with Attachment Dump in. (mm)	61 (1550	
Max. Dump Angle (Deg.) Attachment Rollback Angle (Deg) Breakout Force at Pivot Point (dig position) lb. (kg) Bucket Width in. (mm) Lifting Capacity to Full Height at Pivot Point lb. (kg) Lifting Capacity to Full Height at 500mm Ahead of Pivot Point lb. (kg) Bucket Connection Type Skid Steer Quick Attach Bucket Level Indicator WARRANTY Tractor - Full Machine Tractor - Limited Powertrain 42 42 41 42 41 42 41 477 (670) 1477 (670) 1497 (670) Skid (1220) 1102 (500) 1234 (560) Skid Steer Quick Attach Standard WARRANTY Tractor - Full Machine 3 Years or 2000 Hours	Reach at Maximum Height in. (mm)	34 (860)	
Attachment Rollback Angle (Deg) Breakout Force at Pivot Point (dig position) 1477 (670) Bucket Width in. (mm) Lifting Capacity to Full Height at Pivot Point lb. (kg) Lifting Capacity to Full Height at 500mm Ahead of Pivot Point lb. (kg) Bucket Connection Type Skid Steer Quick Attach Bucket Level Indicator WARRANTY Tractor - Full Machine 3 Years or 2000 Hours Tractor - Limited Powertrain	Reach at Bucket on Ground in. (mm)	63.4 (1610)	
Breakout Force at Pivot Point (dig position) lb. (kg) Bucket Width in. (mm) Lifting Capacity to Full Height at Pivot Point lb. (kg) Lifting Capacity to Full Height at 500mm Ahead of Pivot Point lb. (kg) Bucket Connection Type Skid Steer Quick Attach Bucket Level Indicator WARRANTY Tractor - Full Machine Tractor - Limited Powertrain 1477 (670) 1102 (500) 1234 (560) Skid Steer Quick Attach Standard WARRANTY Tractor - Full Machine 3 Years or 2000 Hours	Max. Dump Angle (Deg.)	42	
Ib. (kg) Bucket Width in. (mm) Lifting Capacity to Full Height at Pivot Point lb. (kg) Lifting Capacity to Full Height at 500mm Ahead of Pivot Point lb. (kg) Bucket Connection Type Skid Steer Quick Attach Bucket Level Indicator WARRANTY Tractor - Full Machine 3 Years or 2000 Hours Tractor - Limited Powertrain 6 Years or 3000 Hours	Attachment Rollback Angle (Deg)	41	
Lifting Capacity to Full Height at Pivot Point lb. (kg) Lifting Capacity to Full Height at 500mm Ahead of Pivot Point lb. (kg) Bucket Connection Type Skid Steer Quick Attach Bucket Level Indicator WARRANTY Tractor - Full Machine 3 Years or 2000 Hours Tractor - Limited Powertrain 6 Years or 3000 Hours	• • • • • • • • • • • • • • • • • • • •	1477 (670)	
Point lb. (kg) Lifting Capacity to Full Height at 500mm Ahead of Pivot Point lb. (kg) Bucket Connection Type Skid Steer Quick Attach Bucket Level Indicator WARRANTY Tractor - Full Machine Tractor - Limited Powertrain 1234 (560) Skid Steer Quick Attach Standard Varanty Tractor - Full Machine 3 Years or 2000 Hours	Bucket Width in. (mm)	48 (1220)	
Ahead of Pivot Point Ib. (kg) Bucket Connection Type Skid Steer Quick Attach Bucket Level Indicator Standard WARRANTY Tractor - Full Machine Tractor - Limited Powertrain Standard Years or 2000 Hours 6 Years or 3000 Hours		1102 (500)	
Bucket Level Indicator Standard WARRANTY Tractor - Full Machine 3 Years or 2000 Hours Tractor - Limited Powertrain 6 Years or 3000 Hours		1234 (560)	
WARRANTY Tractor - Full Machine 3 Years or 2000 Hours Tractor - Limited Powertrain 6 Years or 3000 Hours	Bucket Connection Type	Skid Steer Quick Attach	
Tractor - Full Machine 3 Years or 2000 Hours Tractor - Limited Powertrain 6 Years or 3000 Hours	Bucket Level Indicator	Standard	
Tractor - Limited Powertrain 6 Years or 3000 Hours	WARRANTY		
	Tractor - Full Machine	3 Years or 2000 Hours	
Front-End Loader 1 Year	Tractor - Limited Powertrain	6 Years or 3000 Hours	
	Front-End Loader	1 Year	

*This brochure is for descriptive purposes only. Summit Tractors reserves the right to change the stated specifications and information without notice. Summit Tractors disclaims all representations and warranties, express or implied, and any liability from the use of this brochure. For complete warranty, safety and product information, see your local Summit Tractors retailer or visit www.summittractors.com and download the operator manual. Horsepower (HP) and other specifications are based on various standards or recommended practices. For your safety, Summit Tractors strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.



FULL SERVICE AVAILABLE. FIND A SUMMIT TRACTORS SERVICE DEALER ON THE SUMMIT CONNECT APP OR VISIT SUMMITTRACTORS.COM