EVERYTHING YOU WANT IN A COMPACT TRACTOR

FREQUENTLY ASKED QUESTIONS

Q. WHO MAKES THE TRACTOR?

A. Our Tractors are made to Summit's exact specifications by ITL, manufacturers of quality tractors sold worldwide. Our engines are made by Mitsubishi, and the Goodyear tire & wheel assemblies are made in the U.S. by industry leader Titan

Q. WHERE DO I GET IT SERVICED?

A. Summit Tractors has partnered with Service Dealers located near every location that Summit Tractors are sold. Providing quality service is our top priority

Q. WHAT IS THE WARRANTY?

A. Summit Tractors have the industry's longest full machine warranty at 3 years or 2000 hours and a very competitive limited powertrain warranty of 6 years or 3000 hours

Q. HOW DOES THIS TRACTOR COMPARE TO OTHER NAME BRANDS?

A. Summit Tractors have more standard features than any tractor in its HP class, with levels of performance and quality equal to or better than that of any other brand

Q. DO YOU OFFER FINANCING?

A. No down payment financing is available. See store or visit the financing section of summittractors.com for more information



A Donation is Made by Summit Tractors for Every Tractor Sold



READY TO GO TO WORK

- 24.7 HP Mitsubishi EPA Tier 4 Diesel Engine
- 18 PTO HP, Rear 540 RPM, Mid 2100 RPM
- Hydrostatic Transmission with Side-By-Side Pedals
- One Set Self-Canceling Detent Rear Hydraulic Remotes
- Cruise Control
- 4WD With Differential Lock
- RimGuard™ Liquid Tire Ballast Rear Tires
- 3rd Function Loader Valve with Integrated Joystick

- Projector Headlamps and Rear Work Light
- Skid-Steer Quick Attach and Self-Leveling Loader

SUMMIT.

- 7-Point Trailer Connector and Front Tow Hook
- Goodyear All Condition R14
 Tires
- Foldable and Removeable Side-View Mirrors
- Category 1 3-Pt Hitch with Swinging and Bar Drawbars
- Premium Adjustable Suspension Seat



THE INDUSTRY'S LONGEST FULL MACHINE WARRANTY

Full Machine: 3 years or 2000 Hours Limited Powertrain: 7 years or 3000 Hours



T DOWNLOAD THE MOBILE APP AND GET CONNECTED

SUMMITTRACTORS.COM



SUMMIT TX25H TRACTOR SPECIFICATIONS AND STANDARD FEATURES

Mitsubishi
Natural Aspiration
24.7 (18.4)
18 (13.4)
2500
3
80.42 (1318)
Liquid
Dual Element
12V42A
Glow Plug
Indirect Fuel Injection
6.9 (26)
2-Range Hydrostatic
Side-by-Side Pedals
Standard
11.32 (18.22)
Wet Disc
Hydraulic
Tiyaradire
Open Center
4.8 (18.2)
1
1322 (600)
1168 (530) Position Control
1 Set Self-Canceling Detent
Standard
Standard w/ Loader
T
Independent
Electric/Hydro
2100
540
1 3/8 (35)
Standard
Standard
Standard
Metal
Standard
113.6 (2886)
54 (1372)
61.8 (1570)
92.1 (2340)
9.6 (245) Front Axle
2513 (1140)
152 (3861)
3406 (1545)

STANDARD TIRES

Front	Goodyear R14T 23x8.50-12 (USA)
Rear	Goodyear R14T 12-16.5 (USA)
OPERATOR STATION	
Roll Over Protection Structure (ROPS) Type	Folding
Premium Projector Headlamps	Standard
Rear Work Light	Standard
High Back Seat with Backrest Extension	Standard
Dial by Operator Weight Seat Suspension Adjustment	Standard
Angle Adjustable & Folding Seat Armrests	Standard
Retractable Seat Belt	Standard
Seat Cover Type	Coated PVC Weatherproof
Side View Mirrors	Standard
Heavy Duty Rubber Floor Mat	Standard
Entry Assist Steps & Grab Rails	Both Sides Standard
12V Power Outlet & Cup Holder	Standard
FRONT-END LOADER	
Model	LX85
Mechanical Self-Leveling	Standard
Max Lifting Height at Pivot Point in. (mm)	83 (2108)
Clearance with Attachment Dump in. (mm)	61 (1550
Reach at Maximum Height in. (mm)	34 (860)
Reach at Bucket on Ground in. (mm)	63.4 (1610)
Max. Dump Angle (Deg.)	42
Attachment Rollback Angle (Deg)	41
Breakout Force at Pivot Point (dig position) lb. (kg)	1477 (670)
Bucket Width in. (mm)	48 (1220)
Lifting Capacity to Full Height at Pivot Point Ib. (kg)	1102 (500)
Lifting Capacity to Full Height at 500mm Ahead of Pivot Point Ib. (kg)	1234 (560)
Bucket Connection Type	Skid Steer Quick Attach
Bucket Level Indicator	Standard
WARRANTY	
Tractor - Full Machine	3 Years or 2000 Hours
Tractor - Limited Powertrain	7 Years or 3000 Hours
Front-End Loader	1 Year

*This brochure is for descriptive purposes only. Summit Tractors reserves the right to change the stated specifications and information without notice. Summit Tractors disclaims all representations and warranties, express or implied, and any liability from the use of this brochure. For complete warranty, safety and product information, see your local Summit Tractors retailer or visit www.summittractors.com and download the operator manual. Horsepower (HP) and other specifications are based on various standards or recommended practices. For your safety, Summit Tractors strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.



FULL SERVICE AVAILABLE. FIND A SUMMIT TRACTORS SERVICE DEALER ON THE SUMMIT CONNECT APP OR VISIT SUMMITTRACTORS.COM

FOR MORE INFORMATION VISIT SUMMITTRACTORS.COM