

# COMPATIBLE EQUIPMENT



Please refer to the chart below when selecting 3-Point or Skid Steer Quick-Attach mounted attachments and implements for your Summit TX25H Tractor and LX85 self-leveling loader. This information is presented as general guidelines. Factors such as soil conditions, density and height of brush, depth and consistency of snowfall and center of gravity of material lifted by the loader will present some variability. We recommend that the loader remain attached to provide ballast (counter-weight) to 3-point mounted equipment, and while the rear tires of every Summit Tractor are filled with RimGuard™ Liquid Tire Ballast, stability, safety and loader performance are improved when additional weight is added to the rear of the tractor's 3-point hitch. Always work slowly and carefully when first adding and using attachments & implements to help ensure the proper combination.

The equipment categories appearing in this chart represent the more common types used with compact tractors. For additional equipment not appearing here, please consult the equipment manufacturer's guidelines.

## COMPATIBLE ATTACHMENTS & IMPLEMENTS - 3-POINT OR SKID STEER QUICK-ATTACH MOUNTED

CATEGORY	WORKING WIDTH				HOPPER CAPACITY (LBS.)	TANK GALLON CAPACITY	PALLET FORK LENGTH (INCHES)	RECOMMENDED MAXIMUM WEIGHT OF ATTACHMENT OR IMPLEMENT (LBS.)
	48"	54"	60"	72"				
<b>PTO DRIVEN 3-POINT EQUIPMENT</b>								
ROTARY CUTTERS	X	X	X					
ROTARY TILLERS	X	X						
FINISH (GROOMING) MOWERS	X	X	X					
FLAIL MOWERS	X	X						
SEEDERS/SPREADERS					500			
SPRAYERS						60		
SNOW BLOWERS	X	X	X					
<b>OTHER 3-POINT EQUIPMENT</b>								
BOXPLANE	X		X					
REAR BLADES	X	X	X					
LANDSCAPE RAKES	X	X	X	X				
BOX BLADES (BOX SCRAPERS)	X	X	X					
LAND LEVELERS (LAND PLANES)	X	X	X					
CULTIPACKERS	X	X	X					
DISC HARROWS	X	X						
FIELD CULTIVATORS	X	X	X					
12V SPRAYERS						60		
<b>LOADER MOUNTED EQUIPMENT</b>								
GRAPPLES	X	X						275
PALLET FORKS							36,42,48	250
FRONT BLADES		X	X					
SNOW PUSHERS	X	X	X					