

# SUMMIT TX25H TRACTOR SPECIFICATIONS AND STANDARD FEATURES

ENGINE		STANDARD TIRES	
Engine Manufacturer	Mitsubishi	Front	Goodyear R14T 23x8.50-12 (USA)
Engine Type	Natural Aspiration	Rear	Goodyear R14T 12-16.5 (USA)
Gross Engine Power, HP (kw)	24.7 (18.4)	OPERATOR STATION	
PTO, HP (kw)	18 (13.4)	Roll Over Protection Structure (ROPS) Type	Folding
Rated Engine Speed	2500	Premium Projector Headlamps	Standard
Number of Cylinders	3	Rear Work Light	Standard
Displacement, cu.in. (cc)	80.42 (1318)	High Back Seat with Backrest Extension	Standard
Cooling System	Liquid	Dial by Operator Weight Seat Suspension Adjustment	Standard
Air Cleaner	Dual Element	Angle Adjustable & Folding Seat Armrests	Standard
Alternator	12V42A	Retractable Seat Belt	Standard
Starting Aid	Glow Plug	Seat Cover Type	Coated PVC Weatherproof
Fuel System Type	Indirect Fuel Injection	Side View Mirrors	Standard
Fuel Tank Capacity, U.S. gal. (L)	6.9 (26)	Heavy Duty Rubber Floor Mat	Standard
POWERTRAIN		Entry Assist Steps & Grab Rails	Both Sides Standard
Transmission Type	2-Range Hydrostatic	12V Power Outlet & Cup Holder	Standard
Forward/Reverse Foot Control	Side-by-Side Pedals	FRONT-END LOADER	
Cruise Control	Standard	Model	LX85
Max Traveling Speed, mph (km/h)	11.32 (18.22)	Mechanical Self-Leveling (MSL) System	Standard
Brakes	Wet Disc	Maximum Lift Height to Bucket Pivot Pin, in. (mm)	85 (2160)
Steering	Hydraulic	Lift Capacity to Maximum Height at Pivot Pin, lb. (kg)	925 (420)
HYDRAULIC SYSTEM		Dumping Clearance, in. (mm)	61 (1540)
Pump Type	Open Center	Maximum Dump Angle, degrees	45
Implement Flow, gpm (L/Min)	4.8 (18.2)	Bucket Width, in. (mm)	52 (1310)
Category, 3-Point Hitch	1	Total Weight Loader with Bucket, lb. (kg)	573 (260)
3-Pt. Hitch Lift Capacity, lb. (kg)	1322 (600)	Weight of Bucket, lb. (kg)	176 (80)
At 24 Inches Behind Link Ends, lb. (kg)	1168 (530)	Bucket Connection Type	Skid Steer Quick Attach
Lift Control type	Position Control	Bucket Level Indicator (BLI)	Standard
Rear Remote Valves	1 Set Self-Canceling Detent Standard	WARRANTY	
3rd Function Diverter Valve	Standard w/ Loader	Tractor - Full Machine	3 Years or 2000 Hours
PTO		Tractor - Limited Powertrain	6 Years or 3000 Hours
PTO Type	Independent	Front-End Loader	1 Year
PTO Control	Electric/Hydro	*This brochure is for descriptive purposes only. Summit Tractors reserves the right to change the stated specifications and information without notice. Summit Tractors disclaims all representations and warranties, express or implied, and any liability from the use of this brochure. For complete warranty, safety and product information, see your local Summit Tractors retailer or visit <a href="http://www.summittractors.com">www.summittractors.com</a> and download the operator manual. Horsepower (HP) and other specifications are based on various standards or recommended practices. For your safety, Summit Tractors strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.	
PTO Mid (rpm)	2100		
PTO Rear (rpm)	540		
PTO Shaft Diameter in. (mm)	1 3/8 (35)		
OTHER			
Cross-Bar Type Drawbar	Standard		
Swinging Drawbar	Standard		
Front Tow Hook	Standard		
Hood and Fenders Material	Metal		
Rimguard™ Liquid Tire Ballast Rear Tires	Standard		
DIMENSIONS			
Overall Length, in. (mm) with R14T Tires	113.6 (2886)		
Overall Width, in. (mm) with R14T Tires	54 (1372)		
Wheelbase, in. (mm) with R14T Tires	61.8 (1570)		
Height to Top of ROPS, in. (mm) R14T Tires	92.1 (2340)		
Min. Ground Clearance, in. (mm) R14T Tires	9.6 (245) Front Axle		
Total Weight, lb (kg) R14T Tires & Wheels	2513 (1140)		
Total Length w/Loader, in. (mm)	152 (3861)		
Total Weight w/Loader and Rimguard™ Liquid Tire Ballast Rear Tires, lb. (kg)	3406 (1545)		

